

BGHBM nxt B 260L WH NB SD







Overall Tolerance ±2mm

Industrial LED Highbay "*BLAZE nxt 200W*"

Features

- Pressure die-cast (ADC12) aluminum housing and LED driver compartment.
- Eyebolt provided for suspension mounting.
- LED module fixed on die-cast aluminum heat sink for proper thermal management.
- Optics: Secondary lens optics provided.
- Constant current driver to have built-in surge, open & short circuit protection.
- Completely prewired with accessories up to terminal block.

General Information	
Product Category	LED Industrial Lighting
System Wattage	200W
Luminous Flux (±10%)	26,000 lm
Luminaire efficacy	130 lm/W
Correlated Color Temperature	5700K±355k
Color Rendering Index	>70
Maintenance of lumen output	50,000 hrs.
Operating Temperature Range	-40°C to 50°C
Beam Angle (±10%)	67°

Operating and Electrical	
Input Voltage	140 to 270V AC
Input Frequency	50 HZ
System Current in Amp. @240V AC	0.964A
Power Factor	≥ 0.95
THD	<10%
Built-in Surge Protection	4 kV

Product data and Ordering data	
Product Cat. Ref.	BGHBM nxt B 260L WH NB SD
Product Code	113288
Case Lot	1 No.
Net Weight	2.9 Kg. Approx.

Approval	
Ingress Protection	IP65
Mechanical Impact Protection	IK06

Doc. No.- ILLUM/TDS/1920/IL/236 Rev-01, Dated.26/06/2020

Note: Data subject to variation due to change/improvement in the design, materials and processes.

BAJAJ LUMINAIRES
Making the difference

ILLUMINATION BUSINESS UNIT,
601, Rustomjee Aspiree, Bhanu Shankar Yagnik Marg,
Off Eastern Express Highway, Sion (E), Mumbai – 400 022.
Email : luminaires@bajajelectricals.com