
TENTO nxt B 110L WH NB SD





Overall Tolerance ±2mm

TENTO nxt LED High Bay 100W 857

Industrial LED Highbay

Features

- Pressure die-cast aluminum housing and LED driver compartment.
- Eye-bolt provided for suspension mounting.
- LED fixed on die-cast aluminum heat sink for proper thermal management.
- Optics: Secondary lens optics provided.
- Constant current driver to have built-in surge, open & short circuit protection.
- Completely prewired with accessories up to terminal block.

General Information	
Product Category	LED Industrial Lighting
System Wattage	100W
Luminous Flux (±10%)	11,000 lm
Luminaire efficacy	110 lm/w
Correlated Color Temperature	5700K±355K
Color Rendering Index	>80
Maintenance of lumen output	50,000 hrs.
Operating Temperature Range	-5°C to 45°C
Beam Angle	63°

Operating and Electrical	
Input Voltage	140 to 270V AC
Input Frequency	50/60 HZ
System Current in Amp. @240V AC	0.404A
Power Factor	≥ 0.9
THD	<10%
Built-in Surge protection	4 kV

Product data and Ordering data	
Product Cat. Ref.	TENTO nxt B 110L WH NB SD
Product Code	113297
Case Lot	1 No.
Net Weight	2.75 Kg. Approx.

Approval	
Ingress Protection	IP65
Mechanical impact protection	IK06

Doc. No.-ILLUM/TDS/1920/IL/226 Rev-00, Dated.05/02/2020
Note: Data subject to variation due to change/improvement in the design, materials and processes.

BAJAJ LUMINAIRES
Making the difference

ILLUMINATION BUSINESS UNIT,
601, Rustomjee Aspiree, Bhanu Shankar Yagnik Marg,
Off Eastern Express Highway, Sion (E), Mumbai – 400 022.
Email : luminaires@bajajelectricals.com